

PRICE LIST

Effective: 1st March 2014

KIRLOSKAR BROTHERS LIMITED

Distribution Sector

Motor Segment

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)

List Price: INDUS 3 Squirrel Cage TEFC Motors

Business Terms & Conditions

- The List Prices are not inclusive of central excise duties. Central excise duties are shown separately and include education cess. Central excise duties mentioned here as per rates applicable as on date; however, the same will be charged at the rate prevailing at the time of dispatch.
- VAT / Sales Tax (Central / State), Octroi, Entry tax or any other levy as applicable will be charged extra at the rates prevailing at the time of supply.
- Prices are subject to change without prior notice.
- The Price list mentions kW & HP. HP mentioned is approximate only kW is binding.
- **Extra Charges: Testing and accessories attract ED**
- **Extra Charges: Testing.** In case of Third Party / Customer Inspection following would be inspection charges per motor for witnessing the Tests.

Frame Size	Routine Test	Type Test
Up to 160	2200	5500
180 - 250	3300	8000
280- 335	5500	11000

- **Motor Dispatch under CT3 Bond 5% Extra Cash.**
- **Extra Charges: Vacuum Pressure Impregnation Treatment (VPI).**

Frame Size	Cash Extra
100 - 132	3% Sub to Max Rs. 3000/-
160 - 180	4% Sub to Max Rs. 3500/-
200 - 280	5% Sub to Max Rs. 4000/-
Above 280	Nil

- a) **No extra charges for flange/foot cum flange ratings for 71-132 Frame sizes.**
- b) **Special shaft Extension:- Standard Double Shaft Extension (DE/NDE Identical) 5% Extra Cash**
- c) For any specifications not mentioned herein Vibrator Motor/Ginning Motor/ ISI mark Motors, please contact marketing at KBL Regional Offices.


Prepared By  Pushan Pahari – Industry Segment Head	Approved By  Ashish Tripathi - Sector Head (Distribution)
---	--

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50° C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		2 Pole- 3000 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
1	0.75	KI-80	11150	459
1.5	1.1	KI-80	12150	501
2	1.5	KI-90S	14000	577
3	2.2	KI-90L	18000	742
5	3.7	KI-100L	22000	906
7.5	5.5	KI-112M	32700	1347
7.5	5.5	KI-132S	36000	1483
10	7.5	KI-132S	36200	1491
12.5	9.3*	KI-132M	58100	2394
12.5	9.3*	KI-160M	66000	2719
15	11	KI-160M	67000	2760
20	15	KI-160M	76700	3160
25	18.5	KI-160L	99000	4079
30	22	KI-180M	111000	4573
40	30	KI-200L	165000	6798
50	37	KI-200L	200900	8277
60	45	KI-225M	258000	10630
75	55	KI-250M	348000	14338
100	75	KI-280S	453000	18664
120	90	KI-280M	527000	21712
125	93	KI-280M	530400	21852
150	110	KI-315S	689500	28407
170	125	KI-315M	809000	33331
180	132	KI-315M	840000	34608
200	150	KI-315L	890000	36668
215	160*	KI-315L	923000	38028
240	180*	KI-315L	973000	40088
270	200*	KI-315L	1070000	44084

* Suitable for ambient temperature of 45 Degree C

Prepared By  Pushan Pahari – Industry Segment Head	Approved By  Ashish Tripathi - Sector Head (Distribution)
---	--

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50° C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		4 Pole- 1500 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
0.5	0.37	KI-71	10300	424
0.75	0.55	KI-80	11200	461
1	0.75	KI-80	11600	478
1.5	1.1	KI-90S	13100	540
2	1.5	KI-90L	14300	589
3	2.2	KI-100L	19000	783
5	3.7	KI-112M	24300	1001
7.5	5.5	KI-132S	34000	1401
10	7.5	KI-132M	39000	1607
12.5	9.3*	KI-132M	54000	2225
12.5	9.3*	KI-160M	62500	2575
15	11	KI-160M	62800	2587
20	15	KI-160L	78000	3214
25	18.5	KI-180M	105000	4326
30	22	KI-180L	117500	4841
40	30	KI-200L	158000	6510
50	37	KI-225S	194000	7993
60	45	KI-225M	236000	9723
75	55	KI-250M	324000	13349
80	60	KI-250M	338000	13926
100	75	KI-280S	415000	17098
120	90	KI-280M	481000	19817
125	93	KI-280M	488000	20106
150	110	KI-315S	602000	24802
170	125	KI-315M	687000	28304
180	132	KI-315M	708000	29170
200	150	KI-315L	823000	33908
215	160*	KI-315L	826000	34031
240	180*	KI-315L	884500	36441
270	200*	KI-315L	1010000	41612
300	225*	KI-355L	1033000	42560
335	250*	KI-355L	1109000	45691
350	260*	KI-355L	1111000	45773
370	275*	KI-355L	1123000	46268

Prepared By



Pushan Pahari – Industry Segment Head

Approved By




Ashish Tripathi - Sector Head (Distribution)

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50° C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		6 Pole- 1000 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
0.24	0.18	KI-71	9200	379
1	0.75	KI-90S	14000	577
1.5	1.1	KI-90L	15300	630
2	1.5	KI-100L	19600	808
3	2.2	KI-112M	23800	981
5	3.7	KI-132M	35800	1475
7.5	5.5	KI-132M	39900	1644
10	7.5	KI-160M	64500	2657
12.5	9.3	KI-160L	79000	3255
15	11	KI-160L	80200	3304
20	15	KI-180L	118000	4862
25	18.5	KI-200L	154000	6345
30	22	KI-200L	165000	6798
40	30	KI-225M	242000	9970
50	37	KI-250M	325500	13411
60	45	KI-280S	417000	17180
75	55	KI-280M	490000	20188
90	67	KI-315S	572000	23566
100	75	KI-315S	575000	23690
120	90	KI-315M	726900	29948
125	93	KI-315M	738400	30422
150	110	KI-315L	808000	33290
170	125	KI-315L	881900	36334
180	132	KI-315L	942200	38819
200	150	KI-315L	969200	39931
215	160*	KI-315L	977600	40277
240	180*	KI-355L	1078000	44414

* Suitable for ambient temperature of 45 Degree C

Prepared By  Pushan Pahari – Industry Segment Head	Approved By  Ashish Tripathi - Sector Head (Distribution)
---	--

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		8 Pole-750 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
1.5	1.1	KI-100L	22000	906
2	1.5	KI-112M	25700	1059
3	2.2	KI-132S	33800	1393
5	3.7	KI-160M	67000	2760
7.5	5.5	KI-160M	74100	3053
10	7.5	KI-160L	90000	3708
15	11	KI-180L	128000	5274
20	15	KI-200L	163000	6716
25	18.5	KI-225S	214000	8817
30	22	KI-225M	247500	10197
40	30	KI-250M	353600	14568
50	37	KI-280S	480480	19796
60	45	KI-280M	530400	21852
75	55	KI-315S	598000	24638
100	75	KI-315M	738400	30422
120	90*	KI-315L	842400	34707
150	110*	KI-315L	884000	36421

* Suitable for ambient temperature of 45 Degree C

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		2 Pole- 3000 Rpm Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
12.5	9.3	KI-160MB/D	69300	2855
15	11	KI-160MB/D	70300	2896
20	15	KI-160MB/D	80400	3312
25	18.5	KI-160LB/D	104000	4285
30	22	KI-180MB/D	117500	4841
40	30	KI-200LB/D	173000	7128
50	37	KI-200LB/D	213000	8776
60	45	KI-225MB/D	270000	11124
75	55	KI-250MB/D	365000	15038
100	75	KI-280SB/D	476000	19611
120	90	KI-280MB/D	553000	22784
125	93	KI-280MB/D	556000	22907
150	110	KI-315SB/D	723800	29821
170	125	KI-315MB/D	845000	34814
180	132	KI-315MB/D	880000	36256

Output		4 Pole- 1500 Rpm Flange/Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
15	11	KI-160MB/D	65900	2715
20	15	KI-160LB/D	81900	3374
25	18.5	KI-180MB/D	110000	4532
30	22	KI-180LB/D	123000	5068
40	30	KI-200LB/D	166000	6839
50	37	KI-225SB/D	204000	8405
60	45	KI-225MB/D	247000	10176
75	55	KI-250MB/D	340000	14008
100	75	KI-280SB/D	435000	17922
120	90	KI-280MB/D	505000	20806
125	93	KI-280MB/D	513000	21136
150	110	KI-315SB/D	632000	26038
170	125	KI-315MB/D	722000	29746
180	132	KI-315MB/D	743000	30612

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)

List Price: INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50° C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		6 Pole- 1000 Rpm Flange/Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
10	7.5	KI-160MB/D	67800	2793
12.5	9.3	KI-160LB/D	83000	3420
15	11	KI-160LB/D	84200	3469
20	15	KI-180LB/D	123000	5068
25	18.5	KI-200LB/D	161500	6654
30	22	KI-200LB/D	173000	7128
40	30	KI-225MB/D	254000	10465
50	37	KI-250MB/D	340000	14008
60	45	KI-280SB/D	437000	18004
75	55	KI-280MB/D	514000	21177
100	75	KI-315SB/D	604200	24893
120	90	KI-315MB/D	763200	31444

Output		8 Pole-750 Rpm Flange/Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
5	3.7	160MB/D	70400	2900
7.5	5.5	160MB/D	77700	3201
10	7.5	160LB/D	94400	3889
15	11	180LB/D	135000	5562
20	15	200LB/D	171000	7045
25	18.5	225SB/D	224700	9258
30	22	225MB/D	259800	10704
40	30	250MB/D	371200	15293
50	37	280SB/D	504500	20785
60	45	280MB/D	556900	22944
75	55	315SB/D	627100	25837
100	75	315MB/D	774800	33199

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)


List Price: IE2- INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		IE2-2 Pole- 3000 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
1	0.75	KI-80	12300	507
1.5	1.1	KI-80	13600	560
2	1.5	KI-90S	15600	643
3	2.2	KI-90L	20100	828
5	3.7	KI-100L	24600	1014
7.5	5.5	KI-132S	40600	1673
10	7.5	KI-132S	41800	1722
15	11	KI-160M	74000	3049
20	15	KI-160M	84300	3473
25	18.5	KI-160L	109200	4499
30	22	KI-180M	122500	5047
40	30	KI-200L	182000	7498
50	37	KI-200L	220400	9080
60	45	KI-225M	279000	11495
75	55	KI-250M	376200	15499
100	75	KI-280S	476100	19615
120	90	KI-280M	548000	22578
150	110	KI-315S	710200	29260
170	125	KI-315M	833000	34320
180	132	KI-315M	866500	35700
215	160*	KI-315L	950900	39177
270	200*	KI-315L	1108600	45674

* Suitable for ambient temperature of 45 Degree C

Prepared By



Pushan Pahari – Industry Segment Head

Approved By




Ashish Tripathi - Sector Head (Distribution)

List Price: IE2- INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50° C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		IE2-4 Pole- 1500 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
0.5	0.37	KI-71	11500	474
0.75	0.55	KI-80	12600	519
1	0.75	KI-80	12900	531
1.5	1.1	KI-90S	14600	602
2	1.5	KI-90L	16000	659
3	2.2	KI-100L	21300	878
5	3.7	KI-112M	27200	1121
7.5	5.5	KI-132S	38000	1566
10	7.5	KI-132M	43600	1796
15	11	KI-160M	69000	2843
20	15	KI-160L	85800	3535
25	18.5	KI-180M	115000	4738
30	22	KI-180L	129000	5315
40	30	KI-200L	173000	7128
50	37	KI-225S	213000	8776
60	45	KI-225M	254000	10465
75	55	KI-250M	350000	14420
100	75	KI-280S	431000	17757
120	90	KI-280M	500000	20600
150	110	KI-315S	619000	25503
170	125	KI-315M	708000	29170
180	132	KI-315M	730000	30076
215	160*	KI-315L	851000	35061
270	200*	KI-315L	1040000	42848
335	250*	KI-355L	1140000	46968

* Suitable for ambient temperature of 45 Degree C


Prepared By  Pushan Pahari – Industry Segment Head	Approved By  Ashish Tripathi - Sector Head (Distribution)
---	--

List Price: IE2- INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		IE2-6 Pole- 1000 Rpm Foot Mounted		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
1	0.75	KI-90S	15700	647
1.5	1.1	KI-90L	17100	705
2	1.5	KI-100L	21900	902
3	2.2	KI-112M	26600	1096
5	3.7	KI-132M	40100	1652
7.5	5.5	KI-160M	70000	2884
10	7.5	KI-160M	71000	2925
15	11	KI-160L	88400	3642
20	15	KI-180L	130000	5356
25	18.5	KI-200L	169000	6963
30	22	KI-200L	182000	7498
40	30	KI-225M	266000	10959
50	37	KI-250M	351000	14461
60	45	KI-280S	450000	18540
75	55	KI-280M	530100	21840
100	75	KI-315S	599000	24679
120	90	KI-315M	756000	31147
150	110	KI-315L	840000	34608
170	125	KI-315L	907000	37368
180	132	KI-315L	970000	39964
215	160*	KI-315L	1006000	41447

* Suitable for ambient temperature of 45 Degree C

Prepared By  Pushan Pahari – Industry Segment Head	Approved By  Ashish Tripathi - Sector Head (Distribution)
---	--

List Price: IE2- INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		IE2-2 Pole- 3000 Rpm Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
15	11	KI-160MB/D	77700	3201
20	15	KI-160MB/D	88500	3646
25	18.5	KI-160LB/D	114500	4717
30	22	KI-180MB/D	128600	5298
40	30	KI-200LB/D	191100	7873
50	37	KI-200LB/D	231500	9538
60	45	KI-225MB/D	292800	12063
75	55	KI-250MB/D	394900	16270
100	75	KI-280SB/D	499900	20596
120	90	KI-280MB/D	576000	23731
170	125	KI-315MB/D	874000	36009
180	132	KI-315MB/D	910500	37513

Output		IE2-4 Pole- 1500 Rpm Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
15	11	KI-160MB/D	72400	2983
20	15	KI-160LB/D	90000	3708
25	18.5	KI-180MB/D	121000	4985
30	22	KI-180LB/D	135000	5562
40	30	KI-200LB/D	182000	7498
50	37	KI-225SB/D	224000	9229
60	45	KI-225MB/D	267000	11000
75	55	KI-250MB/D	367000	15120
100	75	KI-280SB/D	453000	18664
120	90	KI-280MB/D	525000	21630
170	125	KI-315MB/D	744000	30653
180	132	KI-315MB/D	765000	31518

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)

List Price: IE2- INDUS 3 Squirrel Cage TEFC Motors

Motors are suitable for voltage 415 V $\pm 10\%$, frequency 50 Hz $\pm 5\%$, Continuous rating (S1 Duty) IP-55 enclosure, with class 'F' insulation suitable for ambient temperature 50°C (temperature rise limited to class "B") and altitude of up to 1000 m above MSL.

Output		IE2-6 Pole- 1000 Rpm Foot Cum Flange		
HP	KW	FRAME SIZE	Price Each	Ex- Duty
10	7.5	160MB/D	74500	3069
15	11	160LB/D	92800	3823
20	15	180LB/D	136000	5603
25	18.5	200LB/D	177800	7325
30	22	200LB/D	191000	7869
40	30	225MB/D	279000	11495
50	37	250MB/D	369000	15203
60	45	280SB/D	472000	19446
75	55	280MB/D	556000	22907
100	75	315SB/D	628400	25890
120	90	315MB/D	792800	32663

Prepared By



Pushan Pahari – Industry Segment Head

Approved By



Ashish Tripathi - Sector Head (Distribution)